



# SuperPole™ with SuperBar™

An award winning, innovative, horizontal pivoting and locking bar that mounts to the SuperPole™. Improve safety with additional gripping and weight bearing support.

## Features and Benefits

### • Innovative.

A gentle lift unlocks the bar. Keep the bar up to move freely. Let the bar down to lock. Provides 8 locking positions around the SuperPole™.

### • Trusted Support.

Push or pull on the bar to assist with sitting, standing and moving. To help prevent a forward fall, the bar will lock if released. Widely prescribed by therapists around the world.

### • Reduce Caregiver Strain.

Maximize the use of available strength while a caregiver supervises. Promotes safe and independent movement.

### • Space Saver.

Great for around the bath or toilet, where limited space can make it difficult for a wheelchair, walker, or rollator.

*Sold as SuperPole™ with SuperBar™, or add SuperBar™ to an existing SuperPole™.*



## Technical Specifications:



SuperBar™	16" / 40 cm length x 1.5" / 3.81 cm diameter grip. Locks every 45° (8 positions). Typically 24-38" / 61-97 cm from floor with limit of 58" / 147cm to ceiling.
SuperPole™	90" / 229 cm x 1.5" / 3.81 cm diameter. White powder coated steel.
Grip Length	20" / 51 cm. Washable, latex free grip.
Floor to Ceiling Range	93" to 99" / 236 to 253 cm (standard).
Expansion Mechanism	1-1/8" fine cut thread. Zinc plated steel jackscrew.
Top Plate	20" / 51 cm length. Top plate rubber will not mark ceiling.
Base Plate	5" / 13 cm diameter. Non-marking, base plate rubber is ribbed for better gripping.
Weight Capacity	300 lbs / 136 kg. Bariatric weight capacity 450 lbs / 205 kg.

## SuperPole™ Accessories (each sold separately):

Uni-Fit Extender™	Increase floor to ceiling range from 100-120" / 254-305 cm. Not to be used with the SuperTrapeze™, Bariatric, & Ultra Models.
SuperPole™ Ultra	<b>Not to be used with the SuperBar™, Safety Island™ or SuperTrapeze™.</b>
Ceiling Plate Extender™	Allows standard ceiling plate 20" / 51 cm length to span 30" / 76 cm with holes for ceiling attachment to 24" / 61 cm ceiling beam centers.